



PAPER

OPEN ACCESS

RECEIVED

23 March 2026

REVISED

22 July 2026

ACCEPTED FOR PUBLICATION

10 August 2026

PUBLISHED

2 September 2026

Original content from
this work may be used
under the terms of the
[Creative Commons
Attribution 4.0 licence](#).

Any further distribution
of this work must
maintain attribution to
the author(s) and the title
of the work, journal
citation and DOI.



Environmental and auto-induced RF-EMF adult and children far-field exposure simulations between 450 MHz and 26 GHz

Robin Wydaeghe^{1,*} , Bram Stroobandt¹ , Silvia Gallucci² , Marta Parazzini² , Gabriella Tognola² , Joe Wiart³ , Günter Vermeeren¹ , Mònica Guxens^{4,5,6,7,8} , Emmeric Tanghe¹ and Wout Joseph¹

¹ Department of Information Technology, Ghent University—imec, WAVES Research Group, Technologiepark-Zwijnaarde 126, 9052 Ghent, Belgium

² Institute of Electronics, Computer and Telecommunication Engineering, National Research Council of Italy (CNR-IEIIT), Piazza Leonardo da Vinci 32, 20133 Milan, Italy

³ Department of Communication and Electronic (COMELEC), Télécom Paris, Institut Polytechnique de Paris, 19 Place Marguerite Perey, 91120 Palaiseau, France

⁴ ISGlobal, Barcelona Institute for Global Health, C/ Doctor Aiguader 88, 08003 Barcelona, Spain

⁵ ICREA, Pg. Lluís Companys 23, 08010 Barcelona, Spain

⁶ Universitat Pompeu Fabra, C/ Doctor Aiguader 88, 08003 Barcelona, Spain

⁷ Spanish Consortium for Research on Epidemiology and Public Health (CIBERESP), Instituto de Salud Carlos III, Av. de Monforte de Lemos 3-5, 28029 Madrid, Spain

⁸ Department of Child and Adolescent Psychiatry/Psychology, Erasmus MC, University Medical Centre, Dr Molewaterplein 40, 3015 GD Rotterdam, The Netherlands

* Author to whom any correspondence should be addressed.

E-mail: robin.wydaeghe@ugent.be

Keywords: RF-EMF exposure, specific absorption rate (SAR), absorbed power density (APD), FDTD, 6G, child dosimetry, beamforming

Supplementary material for this article is available [online](#)

Abstract

Objective. Children's exposure to radio-frequency electromagnetic fields above 6 GHz lacks characterization. No study spans sub-GHz cellular bands to millimeter wave while including child phantoms. This study quantifies the specific absorption rate (SAR) and absorbed power density (APD) in two adult and two child anatomical phantoms across 15 frequencies from 450 MHz to 26 GHz. **Approach.** We performed 550 finite-difference time-domain simulations covering environmental (plane-wave) and auto-induced (beamforming) exposure. SAR and APD were computed following IEC/IEEE 62 704-1 and IEC/IEEE 63 195-4, respectively. The simulations included, for the first time, whole-body dosimetry at 26 GHz in child and adult phantoms, and child APD across 7–15 GHz. Results were normalized to the international commission on non-ionizing radiation protection 2020 reference levels for general public exposure. **Main results.** Children show 1.5–1.9 times higher whole-body SAR than adults at all sub-6 GHz frequencies. A 6 year-old reaches 93% of the 80 mW kg⁻¹ whole-body SAR limit at 2140 MHz, averaged over 12 plane-wave configurations, and 145% in the worst one. Whole-body SAR, not local SAR, determines compliance margins below 6 GHz. Brain SAR decreases by 96% from 450 MHz to 5.8 GHz as absorption shifts to the skin. Eye SAR drops 77-fold from 7 to 26 GHz as penetration depth falls below eyelid thickness. Under simplified maximum ratio transmission (MRT) beamforming, psSAR_{10g} at 3500 MHz exceeds the 2 W kg⁻¹ head/torso limit for all four phantoms (131%–158%). APD at 7 GHz exceeds 20 W m⁻² for a 6 year-old by 2.5%. Worst-case whole-body SAR agrees with the literature within 2%. **Significance.** The results identify frequency-phantom combinations where compliance margins narrow: 3500 MHz and 7 GHz under beamforming, and children near 2 GHz under environmental exposure. The organ-specific SAR data for brain, eyes, skin, and genitals support epidemiological exposure assessment and dose modeling across current and prospective wireless bands.

1. Introduction

With the deployment of 5G wireless technology, the number of base stations and antennas per base station has increased significantly compared to 4G (GSMA 2024). 5G networks now serve 2 billion subscribers across more than 100 countries. 6G targets commercial deployment by 2030 (GSMA 2024). These networks span three frequency ranges: FR1 (450 MHz–6 GHz), FR2 (24–52.6 GHz for 5G mmWave), and the prospective FR3 (7–15 GHz for 6G) (Next G Alliance 2023, Katwe *et al* 2024). When a massive MIMO (MaMIMO) base station beamforms toward an active user, the resulting exposure is *auto-induced* (Velghe *et al* 2021), the user's position induces the exposure. For non-users or 4G users without beamforming, exposure is *environmental*. This distinction matters because auto-induced exposure concentrates energy toward the user, while environmental exposure arrives from all directions. Children's developing tissues may respond differently to radio frequency (RF)–electromagnetic field (EMF) than adults (Peyman *et al* 2009), motivating age-specific exposure assessment.

Computational dosimetry quantifies specific absorption rate (SAR) and absorbed power density (APD) induced in human tissues by external EMF (Hand 2008, Hirata *et al* 2021a). Previous far-field studies characterized whole-body and localized SAR from plane-wave exposure using anatomically realistic phantoms. Dimbylow (2002) established baseline SAR values for an adult model (NORMAN) from 10 MHz to 3 GHz, including scaled child versions. Uusitupa *et al* (2010) extended this to 15 voxel models (18–105 kg) from 300 MHz to 5 GHz. Whole-body SAR at the international commission on non-ionizing radiation protection (ICNIRP) reference level approached basic restrictions for small children. Posture, polarization, and incidence direction significantly affected results. Bakker *et al* (2010) compared induced SAR in child and adult models from 10 MHz to 5.6 GHz, finding that whole-body SAR exceeded the basic restriction by up to 45% in small children at the reference level. Vermeeren *et al* (2008a), Kühn *et al* (2009) showed that reference levels derived from simplified models are not always consistent with basic restrictions when evaluated on detailed anatomical phantoms or realistic multipath environments. Vermeeren *et al* (2008b) applied a stochastic method for assessing whole-body SAR in realistic multipath environments by combining single plane-wave finite-difference time-domain (FDTD) simulations.

These studies focused on sub-6 GHz frequencies and isotropic (environmental) exposure from uniformly distributed plane waves. The ICNIRP 2020 guidelines (ICNIRP 2020) introduced APD as the basic restriction above 6 GHz, replacing volumetric SAR, with a surface metric averaged over 4 cm². Hirata *et al* (2021b) reviewed computational dosimetry studies supporting this transition, confirming that APD correlates with tissue temperature rise at millimeter-wave frequencies. Recent APD studies above 6 GHz used simplified models: planar slabs (Nakae *et al* 2020), spherical heads (Lojić Kapetanović and Poljak 2022), isolated ear structures (Lojić Kapetanović *et al* 2023), typically at single frequencies without cross-phantom comparison. Whole-body average SAR has been computed up to 100 GHz in adult models (Kodera *et al* 2024), but child phantoms have not been included. No study has evaluated APD in realistic whole-body phantoms across the 6G upper mid-band (7–15 GHz), and none has characterized the 'auto-induced' exposure that arises when a MaMIMO base station beamforms toward a user's device. Previous MaMIMO work coupled ray-tracing with FDTD for specific indoor (Shikhantsov *et al* 2020, Wydaeghe *et al* 2022) and outdoor (Wydaeghe *et al* 2026) environments, but these scenario-specific studies do not yield exposure estimates directly comparable across phantoms, frequencies, and technologies.

Three gaps limit current understanding of far-field RF–EMF exposure in the 5G/6G era: (1) No single study spans the full spectral range from sub-GHz cellular bands through the 6G upper mid-band and into millimeter wave (26 GHz) while including child phantoms, capturing how dosimetric metrics evolve as penetration depth decreases from tens of millimeters to one millimeter. (2) Child exposure remains under-characterized at higher frequencies. Existing studies typically include one or two child models, making inter-individual variability difficult to assess. (3) Auto-induced exposure, where beamforming creates localized hotspots near the body, has not been systematically evaluated against ICNIRP 2020 basic restrictions across phantoms and frequencies.

This study addresses these gaps with FDTD simulations covering 15 frequencies (450 MHz–26 GHz), four virtual population (ViP) phantoms (Gosselin *et al* 2014) (two adults, two children), and two exposure scenarios: environmental (isotropic plane-wave illumination from 12 directions with two polarizations each, as in Bakker *et al* (2010), Uusitupa *et al* (2010)) and auto-induced (four-direction MRT beamforming toward a hypothetical user equipment (UE) location). We compute psSAR_{10g}, whole-body SAR, and organ-specific SAR following the IEC/IEEE 62 704–1 standard (IEC/IEEE 2017) below 6 GHz, and APD following the IEC/IEEE 63 195–4 standard (IEC/IEEE 2022) at or above 6 GHz. To the best of the authors' knowledge, this is the first study to perform whole-body dosimetry at 26 GHz in

child phantoms and to characterize child APD across the 7–15 GHz band. The 550 simulations enable comparisons between phantoms and frequency bands revealing how compliance margins with ICNIRP 2020 basic restrictions vary with body size, frequency, and exposure scenario. The comparison reveals a result the reference levels do not account for. At 3500 MHz and 7 GHz, auto-induced beamforming meets the ICNIRP reference level yet exceeds the basic restriction. Below 6 GHz the compliance metric is whole-body SAR. Above it, the metric is APD.

The results inform regulators by identifying frequency-phantom combinations where compliance margins narrow (e.g. 7 GHz auto-induced exposure in child phantoms). The ICNIRP guidelines set no organ-specific basic restriction. Epidemiological studies use organ-level dose to relate exposure to long-term biological outcomes from surveyed usage patterns (Liorni *et al* 2020, Birks *et al* 2021, van Wel *et al* 2021). Such dose modeling requires organ-specific SAR across many frequencies, phantoms, and exposure scenarios. We report an open dataset of the compliance metrics and the organ-specific SAR, for adults and children, from 450 MHz to 26 GHz (GOLIAT Consortium 2022).

2. Methods

Table 1 lists the complete simulation configuration used throughout this section.

2.1. Frequency selection and technology mapping

The 15 frequencies in table 1 span 450 MHz to 26 GHz, covering three spectral regions used by current and future wireless communication systems.

The sub-6 GHz band (FR1) includes nine frequencies representing deployed cellular and Wi-Fi technologies: 450 MHz (LTE Band 31, public safety), 700 MHz (5G NR n28, digital dividend spectrum), 835 MHz (GSM-850), 1450 MHz (LTE Band 32, supplemental downlink), 2140 MHz (LTE Band 1 downlink), 2450 MHz (Wi-Fi 2.4 GHz ISM band), 3500 MHz (5G NR n78, C-band), and 5200/5800 MHz (Wi-Fi 5 GHz UNII bands). These frequencies were selected to sample the most common wireless bands while providing uniform coverage of the RF spectrum up to 6 GHz.

The FR2 band is represented by 26 GHz (5G NR n258). Millimeter-wave bands offer wide contiguous bandwidths (up to 400 MHz per channel), supporting multi-gigabit data rates. High path loss limits practical deployment to short-range, line-of-sight scenarios (Rappaport *et al* 2019). In FDTD simulations, computational cost scales with the fourth power of the frequency (f^4): doubling the frequency halves the cell size in all three dimensions and the time step, increasing workload 16-fold. A single full-body simulation at 26 GHz with 0.3 mm resolution requires several billion grid cells. Therefore, the analysis at this frequency was limited to one phantom (Thelonious) from one incidence direction.

The upper mid-band (7–15 GHz), also referred to as centimeter wave (cmWave) or part of the prospective FR3 frequency range (Next G Alliance 2023), is sampled at five frequencies: 7, 9, 11, 13, and 15 GHz. This spectrum is under active investigation for 6G systems (Katwe *et al* 2024), as it balances the bandwidth limitations of sub-6 GHz bands against the propagation challenges of millimeter-wave frequencies. International regulatory processes are examining spectrum in this range, with the 7.125–8.4 GHz band on the WRC-27 agenda for potential IMT identification (GSMA 2024). FR3 frequencies will become more important for APD compliance as this band will see wider deployment.

2.2. Exposure metrics and normalization

The ICNIRP 2020 guidelines (ICNIRP 2020) define basic restrictions, which are limits on quantities induced within the body (SAR, APD), and reference levels, which are limits on external field quantities that ensure compliance with basic restrictions under typical conditions. This study focuses on the former, with the latter as input power density to determine compliance.


For frequencies below 6 GHz, the relevant basic restriction is the peak spatial SAR over any 10 g cubic mass of tissue ($\text{psSAR}_{10\text{g}}$), computed following IEC/IEEE 62 704–1 (IEC/IEEE 2017). For frequencies at or above 6 GHz, the basic restriction is the APD averaged over any 4 cm² square area, extracted from the skin surface in accordance with IEC/IEEE 63 195–4 (IEC/IEEE 2022).

All simulations were performed with an incident field amplitude of 1 V m^{−1}. Results were subsequently normalized to an incident power density of 1 W m^{−2}, corresponding to an electric field amplitude of $E_0 \approx 27.5$ V m^{−1} in free space. Since SAR scales as E^2 , the normalization factor is $(27.5)^2 \approx 754$. This normalization convention differs from near-field dosimetry, where results are typically normalized to 1 W input power at the antenna feed. For far-field plane-wave illumination, power density is the natural normalization quantity because it is measurable and independent of the source.

Table 1. Comprehensive FDTD Simulation Parameters and Computational Requirements.

Parameter and Unit	Description	5G FR1 / Sub-6 GHz									6G FR3				FR2	
<i>Frequencies and scenarios</i>																
Frequency [MHz]	Sinusoidal	450	700	835	1450	2140	2450	3500	5200	5800	7000	9000	11 000	13 000	15 000	26 000
Technology	Wireless standard	LTE	5G NR	GSM-850	LTE	LTE	Wi-Fi	5G NR	Wi-Fi	Wi-Fi	6G	6G	6G	6G	6G	5G NR
Environmental	Plane wave, isotropic	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Auto-induced	UE beamforming, MRT		✓					✓			✓	✓	✓	✓	✓	
<i>Basic quantities</i>																
SAR [W kg ^{−1}]	Norm. to 1 W m ^{−2}	psSAR _{10g} , SAR _{wb} , SAR _{osa} , SAR _{group} (brain, skin, eyes, genitals), according to IEC/IEEE 62 704-1										Thelonious from one direction				
APD [W m ^{−2}]	Norm. to 1 W m ^{−2}	✗										4-cm ² averaged APD, according to IEC/IEEE 63 195-4				
<i>Spatial and temporal resolution</i>																
Cell size Δx [mm]		2.5	2.5	2.5	2.5	1.694	1.482	1.0	1.0	1.0	0.6	0.5	0.5	0.45	0.4	0.3
Time step Δt [ps]	Courant limit	4.81	4.81	4.81	4.81	3.26	2.85	1.93	1.93	1.93	1.16	0.96	0.96	0.87	0.77	0.58
Perforation [%]	Skin mesh holes	13.1	13.1	13.1	13.1	1.0	0	0	0	0	0	0	0	0	0	0
Cells per δ ₉₀ []	Skin, δ ₉₀ /cell	24	21	19	15	17	18	19	11	10	13	10	8	7	6	4
Cells per 10 g cube side []	21.5 mm / cell	9	9	9	9	13	15	22	22	22	36	43	43	48	54	72
<i>90% power absorption depth δ₉₀</i>																
Eye (Vitreous) [mm]	Bottleneck	36	33	32	28	23	21	15	8.8	7.5	5.6	3.7	2.7	2.1	1.7	0.8
Skin [mm]	Surface (0.5–4 mm)	—	—	—	—	—	—	—	—	—	—	—	3.8	2.9	2.4	1.1
Muscle [mm]	Bulk	59	53	50	39	29	26	17	10	8.7	6.6	4.5	3.3	2.6	2.1	1.1
<i>Cells per wavelength (CPW)</i>																
Eye (Vitreous) []	ε _r : 69→31	32	21	17	10	10	10	10	7	6	9	9	7	7	7	7
Muscle []	ε _r : 57→26	35	23	19	11	11	11	12	8	7	10	10	9	8	8	8
Skin []	ε _r : 46→18	39	26	22	13	13	13	14	10	9	12	12	10	10	10	9
<i>Computational domain size in millions of cells (MCells)</i>																
Height factor h []	(Δx _i /Δx _{7GHz}) ³	1	1	1	1	1	1	1	1	1	1.00	0.58	0.58	0.42	0.30	1
Duke (M, 34y) [MCells]	Full: 54×28×181 cm	28	28	28	28	83	121	376	376	376						✗
	Reduced: x/2×y×z·h										750	744	744	742	740	
Ella (F, 26y) [MCells]	Full: 50×28×163 cm	23	23	23	23	70	103	318	318	318						✗
	Reduced: x/2×y×z·h										630	625	625	623	622	
Eartha (F, 8y) [MCells]	Full: 45×23×139 cm	16	16	16	16	47	69	210	210	210						✗
	Reduced: x/2×y×z·h										408	404	404	403	401	
Thelonious (M, 6y) [MCells]	Full: 37×21×118 cm	11	11	11	11	32	46	142	142	142						
	Reduced: x/2×y×z·h										268	266	266	265	264	
	Half (for SAR): x/2×y×z										241	411	411	559	788	1844

Note: ✗ indicates simulations not performed for that phantom-frequency combination.



2.3. Environmental exposure scenario

Figure 1(a) shows the environmental exposure scenario setup. Environmental exposure occurs when ambient EMF illuminate a subject from all directions. This scenario applies to non-users exposed to base stations and to technologies like 4G LTE that employ omnidirectional transmission rather than user-specific beamforming. In urban environments with multiple base stations and reflections, incident fields arrive from many directions simultaneously.

To characterize this environmental exposure scenario, plane waves were launched from six orthogonal directions aligned with the phantom's anatomical axes: $\pm x$ (left/right), $\pm y$ (front/back), and $\pm z$ (above/-below). For each direction, both θ and ϕ polarizations were simulated, yielding 12 independent FDTD simulations per phantom-frequency combination.

These 12 simulations can be combined to approximate exposure from arbitrary incident directions and polarizations.

2.4. Auto-induced exposure scenario

Figure 1(b) shows the auto-induced exposure scenario with user-specific beamforming. Auto-induced exposure occurs when a MaMIMO base station beamforms toward a user's device, concentrating electromagnetic energy in a localized hotspot near the body. Unlike environmental exposure, the incident field exhibits constructive interference at a focal point determined by the beamforming algorithm. 5G NR and anticipated 6G systems use user-specific beamforming to maximize link quality.

Previous work coupled MaMIMO beamforming with site-specific propagation environments. Hybrid ray-tracing and FDTD methods enable realistic exposure assessment for indoor (Shikhantsov *et al* 2020, Wydaeghe *et al* 2022) and outdoor (Wydaeghe *et al* 2026) scenarios, including stochastic channel models capturing real propagation statistics. These studies show that exposure depends on environment, user position, and channel realization. We take a different approach: rather than modeling specific environments and aggregating across channel realizations, we seek exposure estimates comparable across phantoms and frequencies without statistical bootstrapping (Vermeeren *et al* 2008b, Wydaeghe *et al* 2022).

To simulate this auto-induced exposure scenario, plane waves were launched from four azimuthal directions ($\phi = 270^\circ, 330^\circ, 30^\circ, 90^\circ$) at a fixed co-elevation ($\theta = 90^\circ$), representing a half-space illumination from the phantom's right side. We chose $\theta = 90^\circ$ (horizontal incidence) because base stations are typically mounted at or above head height, making horizontal incidence common, and this geometry maximizes the vertical electric field component E_z . Only θ polarization was considered, as it produces the dominant vertical field component relevant for handheld device coupling (Shikhantsov *et al* 2020).

2.4.1. Beamforming weights

In MaMIMO systems, MRT is a common precoding technique that causes beamforming (Björnson *et al* 2017). For a channel vector $\mathbf{h} \in \mathbb{C}^N$ representing the complex gains from N transmit directions to the UE, the MRT precoding vector (Frobenius-normalized) is

$$\mathbf{w} = \frac{\mathbf{h}^*}{\|\mathbf{h}\|}, \quad (1)$$

which maximizes the received signal power $|y|^2 = \|\mathbf{h}^T \mathbf{w}\|^2$ (Björnson *et al* 2017). Writing each channel element in polar form, $h_i = |h_i| \exp(j\phi_i)$, the weight becomes

$$w_i = \frac{|h_i|}{\|\mathbf{h}\|} \exp(-j\phi_i). \quad (2)$$

The phase term $\exp(-j\phi_i)$ conjugates the channel phase so that all contributions arrive in-phase at the receiver. This is the mechanism that produces constructive interference. The amplitude term $|h_i|/\|\mathbf{h}\|$ allocates more power to directions with stronger channel gains.

In our framework, we interpret each channel h_i as proportional to the vertical electric field component at the UE location due to the i th incident direction: $h_i \propto E_{z,i}(\mathbf{r}_0)$. We assume the UE antenna is vertically polarized, as is typical for handheld devices. Because each h_i is a per-direction channel in the angular domain rather than a per-antenna channel, this is a beamspace formulation of MRT precoding. The amplitude weighting in (2) would require knowledge of which directions have stronger channels, information that depends on the propagation environment.

When simulating many environments using deterministic or stochastic channel models (e.g. ray-tracing or QuaDRiGa (Wydaeghe *et al* 2026)) and averaging the resulting exposure over all channel realizations, no single azimuthal direction consistently dominates. All amplitudes are therefore set to $|w_i| = 1/\sqrt{N}$, yielding

$$w_i = \frac{1}{\sqrt{N}} \exp(-j \arg(E_{z,i}(\mathbf{r}_0))). \quad (3)$$


With this choice, $\|\mathbf{w}\|^2 = 1$ (unit total power) while the phase conjugation of MRT is retained. The combined field at any point $\mathbf{r}$ is then

$$\mathbf{E}_{\text{combined}}(\mathbf{r}) = \sum_{i=1}^N w_i \mathbf{E}_i(\mathbf{r}). \quad (4)$$

We assume perfect channel state information and independent control of each incident direction, such that equation (4) provides an upper bound on the achievable field concentration for a given total transmitted power.

The superposition in equation (4) is exact because the tissue is linear. Each $\mathbf{E}_i$ is a full-wave FDTD solution that already contains the scattering, diffraction, and penetration of wave i into tissue. Therefore, the combined field is defined throughout the body, on the surface and in the interior. psSAR_{10g} is then averaged over a 10 g cubic mass inside tissue (IEC/IEEE 62704–1), and APD over a 4 cm² skin-surface area (IEC/IEEE 63 195–4). The N components together carry the incident power density of one plane wave. The ICNIRP reference level therefore applies directly. Detailed hotspot field maps are reported in Shikhantsov *et al* (2020), Herrens and Thielens (2025) for the same precoding family and phantoms.

Four azimuthal directions balance representativeness against computational cost. In multipath propagation, effective channel rank is limited: singular value decomposition shows that a few principal components capture most channel energy (Björnson *et al* 2017, Wydaeghe *et al* 2022). Four directions spanning the azimuthal half-space capture the dominant modes of typical non-line-of-sight channels while keeping FDTD simulations manageable.



2.4.2. Focus point search

Figure 2 summarizes the worst-case APD search procedure. A MaMIMO base station beamforms toward the UE antenna, held in hand or pocket, always in air, at some distance from skin. Therefore, the beam-forming focus point lies in the air near the body surface, not inside the body. The beam converges at this air location and illuminates nearby skin, where absorption occurs.

The search space comprises air voxels within a 20 mm shell surrounding the phantom surface. This thickness covers realistic UE-to-body distances while excluding voxels too far to produce substantial skin exposure. From this space, 10 000 candidate focus points were randomly sampled, yielding approximately 10 mm average spacing given the 1.8 m² skin surface area of an adult phantom.

For FR3 simulations computing only APD, additional padding of 20 mm (*x*-direction) and 10 mm (*y*-direction) was added to accommodate focus points behind the phantom (e.g. near back or arms). At FR1 frequencies (700 MHz and 3500 MHz), the search shell was widened to 50 mm (from 20 mm at FR3). At sub-GHz wavelengths, a beam focused further from the surface still produces a meaningful hotspot on the skin. The minimum candidate separation was increased to 100 mm, consistent with the 20× longer wavelength at 700 MHz ($\lambda = 430$ mm) compared to FR3. The candidate pool was doubled to 40 per phantom with a lower selection percentile (80% versus 95% at FR3), because proxy correlation is weaker at these frequencies (see section 3.3). At 3500 MHz and at FR3 frequencies, field combination was restricted to a 50 mm cube around each focus voxel. The SAR peak at these frequencies occurs within millimeters of the focus on the skin surface. At 700 MHz, SAR peaks can appear far from the focus point (see section 3.3), so full-volume combination over the entire body was used instead.

2.4.3. Hotspot score for efficient worst-case identification

Identifying the worst-case focus point requires evaluating APD for each candidate location. Full APD extraction following IEC/IEEE 63 195–4 (IEC/IEEE 2022) is computationally expensive: surface integration over 4 cm² averaging areas across the entire phantom surface.

We developed the *hotspot score* that approximates APD without full extraction, exploiting the relationship between electric field intensity and APD. For a given air focus point $\mathbf{r}_0$, the hotspot score is defined as:

$$H(\mathbf{r}_0) = \frac{1}{N_{\text{skin}}} \sum_{k=1}^{N_{\text{skin}}} |\mathbf{E}_{\text{combined}}(\mathbf{r}_k)|^2, \quad (5)$$

where the sum is over all N_{skin} skin voxels within a 50 mm cube centered on $\mathbf{r}_0$, and $\mathbf{E}_{\text{combined}}$ is the weighted field from equation (4) with weights computed for focus point $\mathbf{r}_0$ via equation (3).

The hotspot score works because $APD \propto \sigma|E|^2$, where σ is the tissue conductivity. Computing the hotspot score requires only reading pre-computed E-field values at skin voxel locations and performing the weighted combination. No additional FDTD simulations or surface integrations are needed. This enables rapid evaluation of all 10 000 candidate focus points. Candidates in the top 5% by hotspot score were retained for full APD extraction. To avoid clustering, a minimum separation of 50 mm was enforced: candidates were selected greedily in descending hotspot score order, skipping any candidate within 50 mm of an already-selected point.

2.5. Numerical simulation framework

We performed all simulations using Sim4Life 8.2 (ZMT Zurich MedTech AG 2024), a GPU-accelerated FDTD solver based on the Yee algorithm (Yee 1966, Taflove and Hagness 2005). Uniaxial perfectly matched layer (PML) with 7 absorbing layers terminated the computational domain. The Total-Field/Scattered-Field (TF/SF) formulation (Taflove and Hagness 2005) realized far-field illumination. All sources were harmonic excitations at frequencies listed in table 1, with 1 V m^{-1} incident amplitude. Simulation duration was three times the domain diagonal traversal time in free space (6 cycles at 450 MHz, 500 cycles at 26 GHz).

Given the study scale (550 simulations across 15 frequencies, 4 phantoms, multiple directions and polarizations), we developed an open-source Python framework automating the simulation workflow. Each simulation is defined by a JSON configuration file for reproducibility.

2.6. Computational methodology

Spatial discretization used a frequency-dependent scheme: 2.5 mm cells at 450–1450 MHz (10–32 cells per wavelength (CPW) in vitreous humor), reducing to 1.0–1.7 mm at 2140–5800 MHz, and 0.3–0.6 mm at FR3 frequencies. Time stepping followed the Courant–Friedrichs–Lewy stability limit (Courant *et al* 1928) ($\Delta t = \Delta x_{\min}/(c_0\sqrt{3})$), yielding 4.81 ps at 450 MHz to 0.58 ps at 26 GHz. Grid resolution was chosen to balance numerical accuracy (targeting 10 CPW in high-permittivity tissues), skin mesh perforation (minimized at $\Delta x \leq 1.5 \text{ mm}$), and computational cost (scaling with the fourth power of cell size without domain reduction). The 90% power absorption depth (δ_{90}) decreases from $\sim 60 \text{ mm}$ in muscle at 450 MHz to 1.1 mm in skin at 26 GHz, justifying coarser grids at low frequencies where penetration is deep. At sub-6 GHz frequencies, the absorption is not confined to the skin layer alone. Complete details on discretization strategy, perforation analysis, and δ_{90} calculation are provided in the supplementary information.

2.7. Anatomical phantoms

We used four anatomically realistic human body models from the ViP of the IT'IS Foundation (Gosselin *et al* 2014): two adults and two children, one for each sex. The ViP models (version 3.1) have $500 \mu\text{m}$ isotropic native resolution throughout the body. Duke (adult male, 34y) and Ella (adult female, 26y) represent adults. Thelonious (male, 6y) and Eartha (female, 8y) represent children. Each phantom comprises over 300 anatomical structures with tissue-specific dielectric properties. Frequency-dependent dielectric properties (ϵ_r , σ) and mass density values came from the IT'IS tissue properties database (version 5) (IT'IS Foundation 2024).

In addition to whole-body and peak spatial-average SAR, regional SAR was computed for four anatomical groups relevant to RF exposure assessment: the brain, eyes, skin, and genitals. These regions appear frequently in epidemiological studies and regulatory discussions. Regional SAR is defined as the mass-weighted average of SAR values across all tissues in the group. The *brain group* comprises gray matter, white matter, cerebellum, hippocampus, thalamus, hypothalamus, midbrain, pons, medulla oblongata, hypophysis, pineal body, commissura anterior, commissura posterior, and cerebrospinal fluid. The *eyes group* comprises the cornea, lens, sclera, and vitreous humor. The *skin group* comprises, as defined by Sim4Life, the skin and 'Ear skin' entities. The *genitals group* comprises sex-specific reproductive organs. For male phantoms (Duke, Thelonious) it includes testis, epididymis, prostate, and penis. For female phantoms (Ella, Eartha) it includes ovary, uterus, and vagina.

2.8. Computational efficiency strategies

At FR3 and FR2 frequencies, fine grid resolution produces computational domains with hundreds of millions to billions of cells. Two domain reduction strategies and cloud infrastructure made these simulations tractable.

2.8.1. Half-body symmetry

For incidence directions illuminating only one side of the body (e.g. $+x$ illuminating the right side), the domain was truncated to include only the illuminated half. The boundary was placed at the sagittal mid-plane with PML termination. This works because high-frequency penetration depth is small enough that fields on the illuminated side do not couple to the opposite side. The ‘x/2’ notation in table 1 indicates this reduction. Tissues that straddle the midplane sit against this boundary, so their metrics are excluded where the reduction is used (section 3.2).

2.8.2. Height factor reduction

Above 7 GHz, domain height was further reduced by a frequency-dependent height factor h . We chose 7 GHz as the reference because at this frequency the domain reaches approximately 800 million cells for adult phantoms, a practical limit beyond which GPUs struggle with memory even in multi-GPU configurations. The height reduction starts by removing the lower body (feet and legs), as peak absorption in the auto-induced scenario occurs in the head and upper torso region.

The height factor was computed as:

$$h = \left(\frac{\Delta x_f}{\Delta x_{7\text{GHz}}} \right)^3, \quad (6)$$

where Δx_f is the cell size at frequency f and $\Delta x_{7\text{GHz}} = 0.6$ mm is the reference cell size at 7 GHz. This cubic scaling keeps the number of grid cells roughly constant as frequency increases: the cell counts for Duke, Ella, Eartha, and Thelonious remain within 2% of their 7 GHz values across the entire FR3 band (table 1). At 15 GHz, for example, $h = (0.4/0.6)^3 \approx 0.30$, meaning only the top 30% of the phantom height is simulated.

We validated this reduction against full-body simulations (supplementary information). At 3.5 GHz, removing the lower 70% of the body ($h = 0.30$) changes the local peak metrics, psSAR_{10g} and head-organ SAR, by less than 4%. The reduction is applied only above 7 GHz, where the penetration depth is shorter and the error smaller. The same sweep at 450 MHz moves the metrics by up to 53%, which is why the full body is retained at all frequencies ≤ 7 GHz.

Without this height reduction, simulations at 15 GHz would require approximately 2.8 billion cells per phantom, over three times the 7 GHz baseline. The time step also decreases with frequency (from 1.16 ps at 7 GHz to 0.77 ps at 15 GHz), adding to the computational cost. For the 26 GHz simulation, the height factor approach was not applied ($h = 1$) to compute SAR_{wb} . Instead, only the smallest phantom (Thelonious) was simulated from a single incidence direction, using half-body symmetry reduction. The same single-direction approach was used for Thelonious at FR3 frequencies to allow SAR extraction for comparison with APD (‘Half (for SAR)’ entries in table 1). Even with these simplifications, the 26 GHz simulation required 1.84 billion cells and multiple 48 GB GPUs.

2.8.3. Computational resources and campaign scale

We executed simulations on rented cloud GPU instances (TensorDock) with NVIDIA H100, RTX 5090, and RTX 6000 GPUs, sometimes in multi-GPU workstations, paired with 32–256 GB RAM. Cloud infrastructure was chosen over traditional high-performance computing (HPC) because our HPC options impose quotas and queues, and Sim4Life requires Windows with licensing better suited to workstations.

The campaign comprised 550 individual FDTD runs across all phantom-frequency-direction-polarization combinations. Simulations ranged from 11 million cells (Thelonious at 450 MHz) to 1.84 billion cells (Thelonious at 26 GHz). Computational cost varied considerably due to f^4 scaling. Duke at 450 MHz completes in under 5 min, at 5.8 GHz in 25 min, and at 26 GHz (Thelonious only, half-body) in over 2 h, at which point I/O-bound setup and extraction phases took similar time.


3. Results

The simulations produced a large multi-dimensional dataset. This section summarizes the main findings. Supplementary information contains more data: per-tissue SAR values for each frequency and direction, frequency response curves for individual organs, spatial hotspot maps, and cross-phantom comparisons.

For comparison with ICNIRP basic restrictions for general public exposure, the limits are 0.08 W kg^{-1} for whole-body average SAR, 2 W kg^{-1} for local psSAR_{10g} (head and trunk), and 20 W m^{-2} for APD above 6 GHz (table 2).

Table 2. ICNIRP 2020 basic restrictions for general public exposure (ICNIRP 2020).

Quantity	Frequency range	Limit	Avg. time
psSAR _{10g}	<6 GHz (head/torso)	2 W kg ⁻¹	6 min
psSAR _{10g}	<6 GHz (limbs)	4 W kg ⁻¹	6 min
SAR _{wb}	All frequencies	0.08 W kg ⁻¹	30 min
APD	>6 GHz	20 W m ⁻²	6 min

**Figure 3.** Skin SAR increases 3.2 times while brain SAR decreases 96% across FR1. Mass-averaged SAR by tissue group for Thelonious, averaged across all 12 directions and polarizations. Eyes show a non-monotonic response.

3.1. FR1 environmental exposure

All SAR values in this section are normalized to an incident power density of 1 W m^{-2} . The ICNIRP 2020 reference levels for general public exposure are $S_{\text{ref}} = f_{\text{MHz}}/200 \text{ W m}^{-2}$ for frequencies below 2 GHz, and 10 W m^{-2} at 2 GHz and above. SAR values can be scaled by these factors to obtain values at the reference level.

3.1.1. Penetration depth determines the frequency response

Figure 3 shows the normalized SAR as a function of frequency. The 90% power absorption depth (δ_{90}) on the body decreases from $\sim 60 \text{ mm}$ at 450 MHz to $\sim 10 \text{ mm}$ at 5800 MHz. This shift from volumetric to superficial absorption drives all SAR metrics.

Figure 3 shows opposite trends for different tissue groups. Skin SAR increases by a factor 3.2 between 450 MHz and 5800 MHz, as energy concentrates superficially. Brain SAR decreases by 96% between 450 MHz and 5800 MHz, because skull and overlying tissues absorb most energy before it reaches the brain. Whole-body SAR decreases by a factor 2.1 between 450 MHz and 5800 MHz, because total absorbed power decreases when absorption confines to a thin surface layer.

Figure 4 shows the transition in the brain-to-skin SAR ratio across all phantoms. At 450 MHz, the ratio ranges from 0.74 to 1.05, meaning brain and skin SAR are comparable. As frequency increases, the ratio drops significantly for all phantoms. At 5800 MHz, the ratios decrease to between 0.003 and 0.015. Child phantoms maintain higher relative penetration at high frequencies compared to adults. This two-order-of-magnitude decrease across the FR1 band shows the shift from penetrating to superficial absorption.




Figure 4. Brain-to-skin SAR ratio across phantoms. Brain exposure drops by orders of magnitude relative to skin as frequency increases. Child phantoms show higher relative brain exposure at high frequencies compared to adults.




Figure 5. Ear tissues absorb twice as much power per unit mass as bulk skin. Top 20 tissues ranked by mass-averaged SAR for Thelonious, averaged across all frequencies in FR1 and directions. Cornea, testis, and meniscus also rank in the top 10.

3.1.2. Tissue-specific absorption

Figure 5 ranks the 20 tissues with highest mass-averaged SAR, averaged across all frequencies and directions. Ear cartilage (36.9 mW kg^{-1}) and ear skin (29.5 mW kg^{-1}) absorb significantly more power per unit mass than bulk skin (21.5 mW kg^{-1}). Their peripheral position and thin geometry explain this: the pinna is exposed from multiple directions and lacks underlying tissue to absorb incident energy.

Cornea ranks fifth (16.8 mW kg^{-1}), consistent with the eye's exposed position. Testis ranks ninth (12.2 mW kg^{-1}), receiving substantial frontal exposure despite pelvic shielding from other angles. Meniscus ranks tenth (11.5 mW kg^{-1}). Inside the skull, cerebrospinal fluid (CSF) ranks eighth




Figure 6. Children show 1.5–1.9 times higher whole-body SAR than adults at all frequencies. Error bars indicate standard deviation across the 12 direction-polarization combinations.

(12.5 mW kg⁻¹), higher than gray matter (5.6 mW kg⁻¹) and white matter (3.2 mW kg⁻¹), due to its high water content and conductivity.

For psSAR_{10g}, the 10 g averaging volume smooths tissue-specific variations. Skin dominates (83.5 mW kg⁻¹), followed by subcutaneous fat (81.4 mW kg⁻¹), muscle (75.7 mW kg⁻¹), and bone (73.7 mW kg⁻¹). Small tissues like ear cartilage (7 g total mass) cannot fill a 10 g cube and thus do not appear in the psSAR_{10g} ranking.

3.1.3. Children have higher whole-body SAR than adults

Figure 6 compares whole-body SAR across phantoms. Child phantoms (Thelonious, 6y, and Eartha, 8y) show 1.5–1.9 times higher SAR_{wb} than adults (Duke, Ella) at all frequencies. At 700 MHz, Thelonious reaches 10.1 mW kg⁻¹ versus Duke's 5.5 mW kg⁻¹ (ratio 1.85).

The higher whole-body SAR in children follows from the relationship between SAR, absorption cross section (ACS), and body mass (Bamba *et al* 2015):

$$\text{SAR}_{\text{wb}} = \frac{\text{ACS}_{\text{wb}} \times S}{m} \quad (7)$$

where ACS_{wb} is the whole-body ACS (in m²), S is the incident power density, and m is body mass. Although children have smaller ACS_{wb} than adults (less body surface area), their mass is proportionally much smaller. The ratio ACS_{wb}/ m is approximately 50% higher in a 6 year-old than in an adult, meaning children absorb more power per kilogram of body mass. At sub-GHz frequencies, body dimensions approach fractions of the wavelength ($\lambda = 43$ cm at 700 MHz), potentially producing quasi-resonance effects that differ between body sizes.


3.1.4. Direction and polarization dependence

Table 3 summarizes directional variation for each SAR metric (Thelonious, frequency-averaged values). Similar patterns are observed for the other phantoms: frequency-averaged whole-body SAR varies 2.0–2.3 $\times$ across phantoms, skin 4.5–6.4 $\times$, eyes 20–36 $\times$, and brain 3.6–6.0 $\times$ (all phantoms, see tables S3–S6 in the supplementary information). Genitals show the largest inter-phantom difference in directional variation, ranging from 9–10 $\times$ for females (Ella, Eartha) to 46–67 $\times$ for males (Duke, Thelonious). For Thelonious, eyes show 20-fold variation: frontal exposure yields 28.9 mW kg⁻¹ versus 1.4 mW kg⁻¹ from behind, as the cornea is exposed while the skull shields posteriorly. Genitals show 44-fold variation between frontal and below directions. The body shields the pelvic region from most angles. Brain shows only 4-fold variation: the skull shields from all directions. Whole-body SAR varies 2-fold.

Polarization generally has smaller effect than direction. Figure 7 shows the polarization ratio for different tissue groups and incident directions. The θ/ϕ polarization ratio ranges from 0.8 to 1.6 for skin and whole-body SAR. Genitals are an exception. From below, the ratio reaches 1.8, indicating stronger coupling to vertically polarized fields. From above, it drops to 0.12. The results may be underestimated because material properties from the IT'IS database are isotropic.

Table 3. Directional variation in SAR metrics (Thelonious, frequency-averaged values).

Metric	Max (mW kg ⁻¹)	Min (mW kg ⁻¹)	Max/Min
Eyes SAR	28.9 (front)	1.4 (back)	20×
Genitals SAR	30.5 (front)	0.7 (below)	44×
Brain SAR	6.5 (below)	1.8 (above)	4×
Skin SAR	41.3 (front)	9.2 (above)	4×
Whole-body SAR	10.3 (back)	5.3 (below)	2×

**Figure 7.** Polarization ratio (θ/ϕ) for different tissue groups and incident directions. Values near 1 indicate insensitivity. Genitals show strong polarization sensitivity (ratio = 1.8 from below). Whole-body SAR remains insensitive.

The IT'IS database also assigns age-independent dielectric properties. The child phantoms therefore have child anatomy but adult tissue properties. Age-independent properties are standard in numerical dosimetry (Kühn *et al* 2009, Bakker *et al* 2010, Gosselin *et al* 2014). A closed-form Fresnel analysis shifts the APD and whole-body SAR conservatively, by 6%–10%. This shift is comparable to the 4%–9% that a 10%–20% dielectric-parameter uncertainty propagates onto the same metrics. Our compliance conclusions are therefore robust to a shift of this size, and the supplementary information reports the full analysis.

We collect these effects into one uncertainty budget (supplementary information). The dominant random contributions are the tissue-dielectric spread and the FDTD numerical error. Combined in quadrature, they give an expanded uncertainty of about $\pm 12\%$ on the absorbed-power metrics, at a 95% coverage probability. The age and domain-truncation effects act in one direction, conservatively.

3.1.5. Correlation between SAR metrics

The correlation matrix across all 432 simulation configurations shows that most metrics are independent, with one protective effect. Skin SAR and brain SAR correlate negatively ($r = -0.45$, $p < 0.001$): high skin absorption reduces energy available for deeper penetration. Superficial absorption shields deep tissues.

Whole-body SAR and skin SAR are nearly uncorrelated ($r = -0.04$). At low frequencies, deep tissues (muscle, organs) dominate whole-body SAR. At high frequencies, whole-body SAR decreases even as the skin fraction increases. These opposing trends cancel.

psSAR_{10g} values for different organs are largely independent. Skin and genitals correlate at only $r = 0.14$. Brain and eyes correlate at $r = 0.54$ (both head-region metrics). Worst-case exposure for one organ does not predict worst-case for others.

Table 4. Direction-averaged whole-body SAR at ICNIRP reference levels (FR1). Bold text refers to the maximum in the table.

Freq (MHz)	S_{ref} (W m^{-2})	Duke	Ella	Eartha	Thelonious	% of limit ^a
		(M,34y)	(F,26y)	(F,8y)	(M,6y)	
		Direction-averaged SAR _{wb} (mW kg^{-1})				
450	2.25	12.0	14.2	18.6	20.6	26%
700	3.50	19.2	22.7	30.3	35.5	44%
835	4.18	21.3	25.7	33.1	40.0	50%
1450	7.25	30.5	37.3	48.9	58.2	73%
2140	10.0	36.9	41.2	61.6	74.8	93%
2450	10.0	34.7	37.8	59.0	71.5	89%
3500	10.0	28.9	31.2	49.1	58.4	73%
5200	10.0	24.3	27.6	39.3	44.7	56%
5800	10.0	24.0	27.0	37.5	42.6	53%

^a Maximum across all four phantoms. Basic restriction SAR_{wb} = 80 mW kg^{-1} .

3.1.6. Compliance margins at reference levels

Table 4 compares direction-averaged SAR at the ICNIRP reference levels against the basic restrictions. The reference level S_{ref} increases from 2.25 W m^{-2} at 450 MHz to 10 W m^{-2} at 2 GHz and above. The rightmost column shows the percentage of the basic restriction reached by the maximum SAR value across all four phantoms.

Whole-body SAR peaks near 2140 MHz for all phantoms, giving the tightest compliance margin in the FR1 band. Thelonious reaches 93% of the basic restriction at this frequency. Child phantoms (Thelonious, Eartha) exceed adults by a factor of 1.7–1.9 across all frequencies. Sex accounts for less than 20% variation within each age group. Adult phantoms remain below 52% of the basic restriction at all frequencies.

These values are averaged over the 12 directions. The worst single configuration (front or back incidence) is 1.5–1.6 times higher. Under that configuration both child phantoms exceed the basic restriction near 2140 MHz. Thelonious is at 145% of the limit and Eartha at 122%. Four of the twelve configurations exceed the limit for each of them. Duke and Ella are below 82% in every configuration.

These values occur at the ICNIRP reference level. A ten-country measurement campaign found environmental power densities of 0.33–1.72 mW m^{-2} , three to four orders of magnitude below the 10 W m^{-2} reference level (Veludo *et al* 2025). At the highest measured level, the worst configuration for Thelonious is 4000 times below the basic restriction.

For psSAR_{10g}, margins are substantially larger. Skin psSAR_{10g} reaches 909 mW kg^{-1} at 2140 MHz for Duke at the reference level (45% of the 2000 mW kg^{-1} limit). Brain and eyes psSAR_{10g} reach 178 mW kg^{-1} and 137 mW kg^{-1} , respectively (9% and 7% of the limit). These are direction-averaged values as well. In the worst configuration, Eartha is at 129% of the 2 W kg^{-1} head and torso restriction at 2140 MHz. The peak is located in the hand, where the limb restriction of 4 W kg^{-1} applies instead. Against that restriction, Eartha is at 65%. psSAR_{10g} is therefore below its applicable restriction in every environmental configuration. Whole-body SAR, not local SAR, is the limiting metric for FR1 environmental exposure, for the direction average and for the worst case.

3.2. SAR trends extended to FR3 and FR2

All SAR values in this section are normalized to 1 W m^{-2} incident and cover Thelonious (M, 6y) under right-side illumination (θ polarization) at 7–26 GHz. Brain SAR is excluded: structures at the sagittal cut face of the half-phantom show SAR increasing with frequency, opposite to the physical expectation for deep tissue (PML boundary artifact). Genitals SAR is excluded by the same mechanism: the penis and prostate run along the sagittal midplane and are cut and exposed to the PML face.

3.2.1. Skin and eye SAR across the full band

Figure 8 shows skin SAR, eye SAR, and whole-body SAR from 450 MHz to 26 GHz. Skin SAR continues to rise: 18.6 mW kg^{-1} at 5800 MHz (FR1, right-side), 21.5 mW kg^{-1} at 7 GHz, and 39.8 mW kg^{-1} at




Figure 8. Eye SAR collapses 77-fold from 7 to 26 GHz as penetration depth falls below eyelid thickness. Skin SAR rises through the full band. Mass-averaged SAR for Thelonious. Solid lines: FR1. Dashed lines: FR3 and FR2. Skin and eye SAR: right-side illumination throughout. Whole-body SAR: FR1 solid = 12-direction isotropic average, FR3/FR2 dashed = single right-side direction. Brain and genitals SAR are excluded due to PML boundary artifacts in the FR3 half-phantom.

26 GHz. The δ_{90} on the body falls from ~ 10 mm at 5800 MHz to 1.1 mm in skin at 26 GHz, concentrating absorption in a progressively thinner surface layer.

Eye SAR falls from 4.92 mW kg^{-1} at 5800 MHz to 3.62 mW kg^{-1} at 7 GHz, then to 0.047 mW kg^{-1} at 26 GHz, a 77-fold decrease across FR3 and FR2. The Thelonious phantom has closed eyes. The eyelid skin covers the cornea. At 26 GHz, δ_{90} in skin falls to 1.1 mm, comparable to eyelid thickness, and incident energy is absorbed in the eyelid before reaching the cornea. The FR1/FR3 boundary is smooth for both skin and eye SAR. Whole-body SAR is normalized by the full-body mass. The shadow half absorbs only the diffraction from the plane wave, limited at 7 GHz, so the illuminated half carries the body's absorbed power. The value is 4.0 mW kg^{-1} at 7 GHz (single direction), continuous with the 4.3 mW kg^{-1} 12-direction average at 5800 MHz. The whole-body SAR stays flat near $3.6\text{--}4.0 \text{ mW kg}^{-1}$ across FR3 and FR2.

3.2.2. $ps\text{SAR}_{10g}$ continuation

$ps\text{SAR}_{10g}$ connects smoothly at the band boundary: 63.5 mW kg^{-1} at 5800 MHz, 60.4 mW kg^{-1} at 7 GHz, and 50.3 mW kg^{-1} at 26 GHz. The decrease is 21% from 5800 MHz to 26 GHz. Spatial averaging over 10 g smooths the increasingly confined surface absorption. As energy concentrates in a thinner layer, the peak spread over a fixed 10 g volume changes slowly. The 12-direction isotropic $ps\text{SAR}_{10g}$ at 5800 MHz is approximately 116 mW kg^{-1} , roughly twice the single-direction value. FR3 and FR2 values likewise underestimate the isotropic worst case.

3.3. FR1 auto-induced exposure

All values are normalized to 1 W m^{-2} incident and scale proportionally at the reference level ($S_{\text{ref}} = 3.5 \text{ W m}^{-2}$ at 700 MHz, 10 W m^{-2} at 3500 MHz). ICNIRP (2020) basic restrictions for local SAR are $ps\text{SAR}_{10g} = 2 \text{ W kg}^{-1}$ (head/torso) and 4 W kg^{-1} (limbs). For whole-body exposure, $\text{SAR}_{\text{wb}} = 80 \text{ mW kg}^{-1}$.

3.3.1. $ps\text{SAR}_{10g}$ at 700 MHz and 3500 MHz

Table 5 compares auto-induced and environmental $ps\text{SAR}_{10g}$ and SAR_{wb} at both frequencies. At 3500 MHz, auto-induced $ps\text{SAR}_{10g}$ exceeds the basic restriction for all four phantoms at the reference level. Worst-case values reach 131%–158% of the 2 W kg^{-1} head/torso limit, with the SAR peak located in the torso, chest, or neck for all four phantoms. At 700 MHz, all phantoms comply. Duke and Eartha peak in the lower leg, where the 4 W kg^{-1} limb limit applies, reaching 22% and 30% respectively. Ella and Thelonious peak in the torso (49% and 48% of the 2 W kg^{-1} limit).

For 3500 MHz, the environmental value for Thelonious already reaches 98% of the basic restriction at S_{ref} , and beamforming causes non-compliance for all four phantoms. This scenario uses simplified

Table 5. Auto-induced psSAR_{10g} and SAR_{wb} compared to the environmental worst case. All values at 1 W m⁻² incident. The % limit column gives psSAR_{10g} as a percentage of the applicable local-SAR basic restriction at S_{ref}.

Phantom	700 MHz (S _{ref} = 3.5 W m ⁻²)					3500 MHz (S _{ref} = 10 W m ⁻²)		
	psSAR _{10g} (mW kg ⁻¹)		SAR _{wb} (mW kg ⁻¹)		% limit at S _{ref}	psSAR _{10g} (mW kg ⁻¹)		% limit at S _{ref}
	Env.	Auto.	Env.	Auto.		Env.	Auto.	
Duke (M, 34y)	129	253	6.7	6.5	22% ^a	156	266	133% ^b
Eartha (F, 8y)	173	339	11.2	11.6	30% ^a	159	305	152% ^b
Ella (F, 26y)	168	280	8.3	7.5	49%	135	316	158% ^b
Thelonious (M, 6y)	132	275	12.4	11.7	48%	197	262	131% ^b

^a Peak in lower leg. Limb limit (4 W kg⁻¹) applies.

^b Peak in torso/chest/neck. Head/torso limit (2 W kg⁻¹) applies.

See supplementary information for body-height distributions.

MRT beamforming from four directions and is not an upper bound. Coherent array gain grows with the number of antenna elements (Marzetta *et al* 2016). Richer propagation environments provide more multipath components for constructive interference, so higher local SAR values are physically feasible. Real deployments vary beam direction with user movement and channel dynamics (e.g. with time division multiple access), which reduces time-averaged exposure.

These values occur at the ICNIRP reference level. A ten-country measurement campaign found 2.61–11.12 mW m⁻² at 3500 MHz under continuous worst-case downloading, three orders of magnitude below that level (Veludo *et al* 2025). Realistic exposure is well below the basic restrictions.

At 700 MHz, the environmental value is well within compliance, and beamforming roughly doubles psSAR_{10g} with ample margin to the limit. The weak proxy correlation at 700 MHz (section 3.3.2) means the reported values may not represent the absolute worst case across all possible focus points. The margin to the local-SAR basic restriction (at most 49% at S_{ref}) is large enough that this uncertainty does not affect the compliance conclusion.

SAR_{wb} at 700 MHz is essentially unchanged by beamforming. Auto-induced SAR_{wb} ranges 6.5–11.7 mW kg⁻¹ across phantoms at 1 W m⁻², within the spread of environmental values (4.1–12.4 mW kg⁻¹ across the 12 directions). Coherent focusing redistributes absorption spatially without increasing total absorbed power.

3.3.2. Proxy reliability and candidate search

The hotspot-score proxy that reliably identifies worst-case APD at FR3 performs differently across the two FR1 frequencies. At 3500 MHz, Spearman rank correlation between proxy score and psSAR_{10g} ranges from $\rho = 0.70$ to 0.80 ($p < 0.001$) across phantoms. The worst-case candidate ranks within the top 8 for all phantoms (top 2 for Duke and Ella, top 1 for Thelonious).

At 700 MHz, rank correlation drops to $\rho = 0.27$ –0.42. Duke's worst case ranks 36th of 40 by proxy score. At this frequency ($\lambda = 430$ mm), body dimensions approach resonance, diffraction wraps fields around the body, and the SAR peak location decouples from the beam focus point. Duke illustrates the effect: the focus voxel lies in the head region, yet the SAR peak occurs in the lower leg (10% of body height). The proxy predicts near-surface field concentration but not deep-tissue absorption at sub-GHz wavelengths (see supplementary material for focus-z vs. peak-z scatter plots). A larger candidate pool of 40 per phantom compensated for the proxy's weak discriminating power at 700 MHz.

3.4. FR3 auto-induced exposure

All APD values in this section are normalized to an incident power density of 1 W m⁻². At the ICNIRP reference level of 10 W m⁻² (applicable above 2 GHz), values scale by a factor of 10. The basic restriction is APD = 20 W m⁻² averaged over 4 cm².

3.4.1. ICNIRP limit exceeded at 7 GHz

Figure 9 shows each phantom's APD as a percentage of the basic restriction across the FR3 band. Thelonious (6y) reaches 103% of the basic restriction at 7 GHz, the only configuration exceeding the ICNIRP limit. Worst-case APD at the reference level is 20.5 W m⁻², exceeding the 20 W m⁻² limit by




Figure 9. Thelonious (6y) exceeds the ICNIRP basic restriction at 7 GHz (103%). Percentage of the basic restriction versus frequency for auto-induced exposure at 10 W m^{-2} reference level. Shaded region above 100% indicates non-compliance. At 15 GHz, all phantoms fall below 40%.

Table 6. Worst-case APD by phantom and frequency (W m^{-2} at 1 W m^{-2} incident).

Phantom	7 GHz	9 GHz	11 GHz	13 GHz	15 GHz
Duke	1.84	1.19	0.86	0.65	0.50
Ella	1.98	1.77	1.31	0.92	0.81
Eartha	1.88	1.40	1.00	0.65	0.74
Thelonious	2.05	1.31	0.86	0.57	0.61

2.5%. Previous studies have reported exceedances of basic restrictions when reference levels are met, particularly for small children at lower frequencies (Vermeeren *et al* 2008a).

At 7 GHz, all phantoms reach 90% or more of the basic restriction: Duke (92%), Eartha (94%), Ella (99%), and Thelonious (103%). Compliance margins improve at higher frequencies: at 15 GHz, all phantoms fall below 40% of the basic restriction. The wavelength-to-averaging-area relationship explains this: at 7 GHz ($\lambda = 43 \text{ mm}$), the MRT-focused beam forms a hotspot comparable to the 4 cm^2 averaging area, maximizing averaged power density. At 15 GHz ($\lambda = 20 \text{ mm}$), the smaller hotspot size spreads power over less of the averaging region.

3.4.2. Peak APD decreases with frequency

Table 6 lists worst-case APD for each phantom-frequency combination. Peak APD decreases 3–4 $\times$ from 7 GHz to 15 GHz for all phantoms. Thelonious shows the highest value at 7 GHz (2.05 W m^{-2} at 1 W m^{-2} incident). Duke shows the lowest (1.84 W m^{-2}). The child-to-adult ratio is approximately 1.1 at 7 GHz, smaller than the 1.5–1.9 ratio for whole-body SAR in FR1.

3.4.3. MRT focuses the vertical field component

Four-direction MRT beamforming generates constructive interference along the vertical (z) axis. Peak E_z at the hotspot is approximately 1.8 V m^{-1} at 1 W m^{-2} incident. E_x and E_y are 0.8 – 0.9 V m^{-1} . The vertical component is thus $2\times$ stronger than horizontal components, as expected for vertical UE antenna orientation.

Hotspot locations distribute across torso, neck, and head. Torso shows highest hotspot scores (~ 250 – $315 \text{ V}^2 \text{ m}^{-2}$). Extremities (feet, hands) show $5\times$ lower values (~ 40 – $80 \text{ V}^2 \text{ m}^{-2}$). All four phantoms exhibit this pattern.

3.4.4. Hotspot score predicts APD

Figure 10 shows the relationship between hotspot score (equation (5)) and measured APD for all $20 \times 4 \times 5 = 400$ candidate hotspots. Linear regression yields

$$\text{APD} = 0.0050 \times H + 0.16 \quad (R^2 = 0.79, p \approx 0) \quad (8)$$




Table 7. Comparison with whole-body SAR from the literature: Dimbylow (2002), Bakker *et al* (2010), Uusitupa *et al* (2010), and the closed-form model of Kodera *et al* (2024). All values are SAR_{wb} in $mW\ kg^{-1}$ for a single plane-wave configuration at $1\ W\ m^{-2}$ incident. Ratio is this work divided by the literature value.

Phantom	Worst case near the 2 GHz peak						Duke, front ^c				Thelonious, side ^d			
	Bakker (2010) ^a			Uusitupa (2010) ^b			Dimbylow (2002)				Kodera (2024)			
	Theirs	Ours	Ratio	Theirs	Ours	Ratio	MHz	Theirs	Ours	Ratio	GHz	Theirs	Ours	Ratio
Duke	6.24	6.21	1.00	6.16	5.77	0.94	400 (450)	6.29	6.34	1.01	7	3.29	3.96	1.20
Ella	6.76	6.60	0.98	7.53	6.60	0.88	900 (835)	6.40	6.45	1.01	11	3.34	3.88	1.16
Eartha	9.68	9.76	1.01	—	—	—	1400 (1450)	6.33	6.11	0.96	15	3.40	3.85	1.13
Thelonious	11.60	11.61	1.00	12.32	11.61	0.94	2450	4.75	5.48	1.15	26	3.61	3.57	0.99
							3000 (3500)	3.99	4.55	1.14				

^a Eartha and Thelonious from their text, Duke and Ella from their figure 4 with the corrigendum applied. ^b Sampled at 2100 MHz, at the polarization they report: vertical for Duke and Thelonious, horizontal for Ella. Our value is the maximum over our directions at the same polarization. Their VF Male, VF Female and VF Boy are the same subjects as Duke, Ella and Thelonious. They do not include Eartha. ^c NORMAN, 73 kg against 72.6 kg for Duke. Our frequency in parentheses where it differs. ^d Closed-form model $ACS_{wb} \approx ApT$, with $Ap = 0.132\ m^2$ the lateral projected area of Thelonious and T the Fresnel power transmission coefficient of skin.

where H is the hotspot score in $V^2\ m^{-2}$ and APD is in $W\ m^{-2}$.
The frequency-dependent clustering is evident: 7 GHz candidates (black) occupy the upper-right region with high hotspot scores (200–350 $V^2\ m^{-2}$) and high APD (1.5–2.0 $W\ m^{-2}$). 15 GHz candidates (orange) occupy the lower-left region. The efficient hotspot score reliably predicts actual APD, confirming that the two-stage screening successfully identifies the candidates with the highest values.

3.5. Comparison with literature

Studies in the literature report the worst single plane-wave configuration. Table 4 gives the average over the 12 configurations, which is 1.5–1.6 times lower. We therefore compare with the per-configuration values, listed in table 7.
Bakker *et al* (2010) simulate the same four phantoms and the same 12 plane-wave configurations. They report 145% (Thelonious) and 121% (Eartha) of the basic restriction, against 145% and 122% in this work. The four worst-case whole-body SAR values differ by at most 2%. Uusitupa *et al* (2010) simulate three of the same phantoms and report 154% for Thelonious. The three values differ by at most 12%. Kühn *et al* (2009) find the 6 year-old phantom above the restriction at 100 MHz and above

1450 MHz. The worst configuration in this work first exceeds it at 1450 MHz. All of these differences are within the expanded uncertainty of $\pm 12\%$ ($k = 2$).

Dimbylow (2002) simulate NORMAN, a different phantom. Its mass is 73 kg, against 72.6 kg for Duke. The agreement is within 4% up to 1450 MHz. Above 2450 MHz Duke absorbs 14%–15% more. NORMAN is a 2.077 mm voxel model, under 7 CPW in muscle at 3 GHz. Coarse voxels under-resolve the body surface, where absorption is concentrated at these frequencies.

No whole-body SAR for a child phantom has been reported above 6 GHz. For FR3 and FR2 we therefore compare against the closed-form model of Kodera *et al* (2024). Above 10 GHz the absorption cross section of equation (7) converges to $ACS_{wb} \approx A_p T$ to within 5%. Here A_p is the projected area of the body seen from the direction of incidence, and T is the Fresnel power transmission coefficient at the skin surface. For Thelonious under side illumination $A_p = 0.132 \text{ m}^2$. The model gives 3.61 mW kg^{-1} at 26 GHz, against 3.57 mW kg^{-1} in this work. The excess over the model falls monotonically from 20% at 7 GHz to 1% at 26 GHz, as expected in the geometric-optics limit. The model omits diffraction into the shadow region. This contribution decreases as the body becomes electrically larger.

4. Conclusion

We characterized RF–EMF exposure from 450 MHz to 26 GHz using 550 FDTD simulations across four phantoms, two exposure scenarios, and 15 frequencies. Environmental whole-body SAR exceeds the basic restriction for both child phantoms near 2140 MHz, in four of the twelve plane-wave configurations. The adult phantoms stay below the restriction in every configuration. Under beamforming, basic restrictions are exceeded when the reference levels are met at 3500 MHz (psSAR_{10g}: 131%–158% of the head/torso limit for all four phantoms) and at 7 GHz (APD: 103% for a 6-year-old). At 700 MHz, beamforming doubles psSAR_{10g} with all phantoms remaining within limits. SAR_{wb} remains unchanged. Coherent focusing redistributes absorption spatially without increasing total absorbed power. At 15 GHz, compliance margins widen to 25%–40% of the basic restriction. These results indicate that ICNIRP reference levels at 3500 MHz and 7 GHz do not guarantee compliance with basic restrictions when beamforming concentrates energy on the body. Reference levels were derived from uniform plane-wave exposure at a fixed incident power density and do not account for this scenario. The equal-power components combine in phase at the focus point, so local absorption concentrates while the incident power density stays at the reference level. At 3500 MHz the volumetric 10 g psSAR_{10g} in the torso exceeds the limit, and at 7 GHz the 4 cm^2 surface APD exceeds it. Measured exposure in deployed 5G networks stays three to four orders of magnitude below this reference level (Veludo *et al* 2025), so realistic exposure remains well below the basic restrictions.

Children show 1.5–1.9 times higher whole-body SAR than adults at all sub-6 GHz frequencies. Their higher ratio of absorption cross section to body mass (equation (7)) explains this difference. At 2140 MHz, Thelonious reaches 93% of the 80 mW kg^{-1} limit averaged over the 12 configurations, and 145% in the worst one. This is the tightest FR1 margin. Whole-body SAR determines FR1 compliance margins. psSAR_{10g} reaches only 45% of its limit when whole-body SAR reaches 93%, and stays below its applicable restriction in every environmental configuration. Worst-case whole-body SAR agrees with the literature within 2% for the same four phantoms, and with a closed-form absorption-cross-section model within 1% at 26 GHz.

Penetration depth determines tissue-specific absorption. Lower frequencies lead to higher absorption in deep tissues. Brain SAR decreases 96% from 450 MHz to 5.8 GHz. Skin SAR increases 3.2-fold as δ_{90} drops from $\sim 60 \text{ mm}$ to $\sim 10 \text{ mm}$. Skin and brain SAR correlate negatively ($r = -0.45$, $p < 0.001$) because superficial absorption shields deep tissues such as the brain.

Four phantoms limit inter-individual variability assessment. More child models (ages 1–17) would strengthen child-adult comparisons. The 26 GHz analysis includes only Thelonious from one direction due to computational constraints. Auto-induced simulations use simplified MRT beamforming from four directions, not environment-specific channel statistics. Actual exposure depends on propagation conditions, antenna count, and scattering richness. All phantoms were simulated in standing configuration. Seated and prone positions may differ in absorption levels.

The organ-specific SAR data for brain, eyes, skin, and genitals support epidemiological exposure assessment across 15 frequencies. The 7.125–8.4 GHz band is on the WRC-27 agenda. Compliance assessment at this band should include child phantoms.

Several extensions merit investigation. Posture variations (seated, prone, moving) would quantify how absorption differs from the standing configuration used here. Coupling this framework with realistic propagation channels (Shikhantsov *et al* 2020, Wydaeghe *et al* 2022, 2026) would quantify how exposure

scales with multipath components and antenna elements across environments. This would extend the results beyond the simplified equal-gain scenario used here. Full characterization of FR2 (24–52.6 GHz) and beyond across all phantoms would complete the 5G and 6G spectrum coverage. As whole-body FDTD simulations become infeasible, other techniques such as those based on the absorption cross section should be used Kodera *et al* (2024). Comparison with temperature-rise measurements or *in vivo* exposure data would validate the computational predictions and strengthen the link between dosimetric quantities and biological outcomes.

Data availability statement

The code to produce all the results is available on GitHub at <https://github.com/rwydaegh/goliat>. The FDTD simulation configuration files and post-processed SAR/APD datasets support-675 ing this study are openly available on Harvard Dataverse at <https://doi.org/10.7910/DVN/EEEE0X>. The Virtual Population phantoms are available from the IT'IS Foundation under license. The software to produce the results is given in the Supplementary Information and requires licenses for the Sim4Life software from Zurich MedTech AG.

Supplementary Information available at: <https://doi.org/10.1088/1361-6560/ae97ac/data1>.

Supplementary Results available at: <https://doi.org/10.1088/1361-6560/ae97ac/data2>.

Funding

The GOLIAT project has received funding from the European Union's Horizon Europe research and innovation programme under Grant Agreement No. 10 105 7262. Views and opinions expressed are however those of the authors only and do not necessarily reflect those of the European Union or the European Health and Digital Executive Agency. Neither the European Union nor the granting authority can be held responsible for them.

Author contributions

R Wydaeghe: Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Data curation, Writing—Original Draft, Visualization. B Stroobandt: Writing—Review & Editing. G Vermeeren: Writing—Review & Editing. E Tanghe: Writing—Review & Editing. W Joseph: Conceptualization, Supervision, Project administration, Funding acquisition, Writing—Review & Editing. S Gallucci, M Parazzini, G Tognola, J Wiart, M Guxens: Conceptualization, Writing—Review & Editing, Funding acquisition.

Conflict of interest

The authors declare no conflicts of interest.

ORCID iDs

Robin Wydaeghe  0000-0002-1374-0118
Bram Stroobandt  0000-0003-2377-4300
Silvia Gallucci  0009-0000-0481-1554
Marta Parazzini  0000-0001-9008-7530
Gabriella Tognola  0000-0002-2433-449X
Joe Wiart  0000-0002-8902-5778
Günter Vermeeren  0000-0002-5309-3808
Mònica Guxens  0000-0002-8624-0333
Emmeric Tanghe  0000-0003-0020-6466
Wout Joseph  0000-0002-8807-0673

References

- Alliance N G 2023 Terminology for frequency ranges white paper (available at: https://nextgalliance.org/white_papers/terminology-for-frequency-ranges/)
- Bakker J F, Paulides M M, Christ A, Kuster N and van Rhoon G C 2010 Assessment of induced SAR in children exposed to electromagnetic plane waves between 10 MHz and 5.6 GHz *Phys. Med. Biol.* **55** 3115–30
- Bamba A, Gaillot D P, Tanghe E, Vermeeren G, Joseph W, Lienard M and Martens L 2015 Assessing whole-body absorption cross section for diffuse exposure from reverberation chamber measurements *IEEE Trans. Electromagn. Compat.* **57** 27–34
- Birks L E *et al* 2021 Radio frequency electromagnetic fields from mobile communication: description of modeled dose in brain regions and the body in European children and adolescents *Environ. Res.* **193** 110505
- Björnson E, Hoydis J and Sanguinetti L 2017 Massive MIMO Networks: spectral, energy and hardware efficiency *Found. Trends Signal Process.* **11** 154–655
- Courant R, Friedrichs K and Lewy H 1928 Über die partiellen Differenzengleichungen der mathematischen Physik *Math. Ann.* **100** 32–74
- Dimbylow P J 2002 Fine resolution calculations of SAR in the human body for frequencies up to 3 GHz *Phys. Med. Biol.* **47** 2835–46
- GOLIAT Consortium 2022 5G expOsure, causaL effects, and rIsk perception through citizen engAgementT Horizon Europe Project No. 101057262 (available at: <https://projectgoliat.eu/>)
- Gosselin M-C 2014 Development of a new generation of high-resolution anatomical models for medical device evaluation: The Virtual Population 3.0 *Phys. Med. Biol.* **59** 5287–303
- GSMA 2024 WRC-23 and WRC-27 – Mobile Spectrum (available at: www.gsma.com/connectivity-for-good/spectrum/wrc-series/)
- Hand J W 2008 Modelling the interaction of electromagnetic fields (10 MHz–10 GHz) with the human body: methods and applications *Phys. Med. Biol.* **53** R243–86
- Herssens H and Thielens A 2025 Auto-induced downlink radio frequency electromagnetic field exposure at 3.5 GHz with focusing near the head *IEEE Access* **13** 56659–70
- Hirata A *et al* 2021a Assessment of human exposure to electromagnetic fields: Review and future directions *IEEE Trans. Electromagn. Compat.* **63** 1619–30
- Hirata A, Kodera S, Sasaki K, Gomez-Tames J, Laakso I, Wood A, Watanabe S and Foster K R 2021b Human exposure to radio frequency energy above 6 GHz: review of computational dosimetry studies *Phys. Med. Biol.* **66** 08TR01
- ICNIRP 2020 Guidelines for limiting exposure to electromagnetic fields (100 kHz to 300 GHz) *Health Phys.* **118** 483–524
- IEC/IEEE 2017 62704-1:2017 Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body From Wireless Communications Devices, 30 MHz–6 GHz – Part 1: General Requirements for Using the Finite-Difference Time-Domain (FDTD) Method
- IEC/IEEE 2022 63195-2:2022 (IEC/IEEE 63195-4) Assessment of power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body (frequency range of 6 GHz to 300 GHz)–Part 2: Computational procedure (<https://doi.org/10.1109/ieeestd.2022.9770556>)
- IT'IS Foundation 2024 Tissue properties database V5.0 (available at: <https://itis.swiss/virtual-population/tissue-properties/database/>)
- Katwe M V, Kaushik A, Singh K, Di Renzo M, Sun S, Lee D, Armada A G, Eldar Y C, Dobre O A and Rappaport T S 2024 CmWave and Sub-THz: key radio enablers and complementary spectrum for 6G *IEEE Wirel. Commun.* **32** 182–90
- Kodera S, Taguchi K, Diao Y, Kashiwa T and Hirata A 2024 Computation of whole-body average SAR in realistic human models from 1 to 100 GHz *IEEE Trans. Microw. Theory Tech.* **72** 91–100
- Kühn S, Jennings W, Christ A and Kuster N 2009 Assessment of induced radio-frequency electromagnetic fields in various anatomical human body models *Phys. Med. Biol.* **54** 875–90
- Liorni I, Capstick M, van Wel L, Wiart J, Joseph W, Cardis E, Guxens M, Vermeulen R and Thielens A 2020 Evaluation of specific absorption rate in the far-field, near-to-far field and near-field regions for integrative radio frequency exposure assessment *Radiat. Prot. Dosimetry* **190** 459–72
- Lojić Kapetanović A and Poljak D 2022 Assessment of incident power density on spherical head model up to 100 GHz *IEEE Trans. Electromagn. Compat.* **64** 1296–303
- Lojić Kapetanović A, Sacco G, Poljak D and Zhadobov M 2023 Area-averaged transmitted and absorbed power density on a realistic ear model *IEEE J. Electromagn. RF Microw. Med. Biol.* **7** 39–45
- Marzetta T L, Larsson E G, Yang H and Ngo H Q 2016 *Fundamentals of Massive MIMO* (Cambridge University Press)
- Nakae T, Funahashi D, Higashiyama J, Onishi T and Hirata A 2020 Skin temperature elevation for incident power densities from dipole arrays at 28 GHz *IEEE Access* **8** 26863–71
- Peyman A, Gabriel C, Grant E H, Vermeeren G and Martens L 2009 Variation of the dielectric properties of tissues with age: The effect on the values of SAR in children when exposed to walkie-talkie devices *Phys. Med. Biol.* **54** 227–41
- Rappaport T S, Xing Y, Kanhere O, Ju S, Madanayake A, Mandal S, Alkhateeb A and Trichopoulos G C 2019 Wireless communications and applications above 100 GHz: opportunities and challenges for 6G and beyond *IEEE Access* **7** 78729–57
- Shikhantsov S, Thielens A, Vermeeren G, Demeester P, Martens L, Torfs G and Joseph W 2020 Massive MIMO propagation modeling with user-induced coupling effects using ray-tracing and FDTD *IEEE J. Sel. Areas Commun.* **38** 1955–63
- Taflov A and Hagness S C 2005 *Computational Electrodynamics: The Finite-Difference Time-Domain Method* 3rd edn (Artech House)
- Uusitupa T, Laakso I, Ilvonen S and Nikoskinen K 2010 SAR variation study from 300 to 5000 MHz for 15 voxel models including different postures *Phys. Med. Biol.* **55** 1157–76
- van Wel L *et al* 2021 Radio-frequency electromagnetic field exposure and contribution of sources in the general population: an organ-specific integrative exposure assessment *J. Expo. Sci. Environ. Epidemiol.* **31** 999–1007
- Velghe M, Aerts S, Martens L, Joseph W and Thielens A 2021 Protocol for personal RF-EMF exposure measurement studies in 5th generation telecommunication networks *Environ. Health* **20** 36
- Veludo A F *et al* 2025 Assessing radio frequency electromagnetic field exposure in multiple microenvironments across ten European countries with a focus on 5G *Environ. Int.* **200** 109540
- Vermeeren G, Joseph W and Martens L 2008a Whole-body SAR in spheroidal adult and child phantoms in realistic exposure environment *Electron. Lett.* **44** 790–1
- Vermeeren G, Joseph W, Olivier C and Martens L 2008b Statistical multipath exposure of a human in a realistic electromagnetic environment *Health Phys.* **94** 345–54

- Wydaeghe R, Shikhantsov S, Tanghe E, Vermeeren G, Martens L, Demeester P and Joseph W 2022 Realistic human exposure at 3.5 GHz and 28 GHz for distributed and collocated MaMIMO in indoor environments using hybrid ray-tracing and FDTD *IEEE Access* **10** 130996–1004
- Wydaeghe R, Shikhantsov S, Vermeeren G, Martens L, Tanghe E and Joseph W 2026 Hybrid ray-tracing-QuaDRiGa/FDTD method for realistic human exposure assessment at 28 GHz with 6G CF-MaMIMO in 3D outdoor environments *npj Wirel. Commun.* **2** 13
- Yee K S 1966 Numerical solution of initial boundary value problems involving Maxwell's equations in isotropic media *IEEE Trans. Antennas Propag.* **14** 302–7
- ZMT Zurich MedTech AG 2024 Sim4Life: Computational Life Sciences Platform (available at: <https://sim4life.swiss/>)